NSN 6625-01-272-3482

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-272-3482

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

4.743 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.346 inches and 3.406 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Mounting Hole Diameter:

0.250 inches

Scale Division Quantity:

100 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

End Application:

Supply class aoe; wasp class lhd; usns henry j. Kaiser class tao; nimitz class cvn

Furnished Items And Quantity:

Nut 6; washer 6; spool res 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.813 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving coil, permanent magnet

NSN 6625-01-272-3482

Ammeter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-200.0/+200.0 amperes single indicator single range
Features Provided:
External shunting and zero adjuster
Criticality Code Justification:
Feat
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized; weapon system essential
Material:
Plastic
Surface Treatment:
Enamel
Special Test Features:
Conforms to mil-m-16034/2
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A310a0