White single indicator single range

Electrical Frequency Meter - Page 1 of 2



resistant and

View Online at https://aerobasegroup.com/nsn/6625-01-273-2918

Circuit Current For Which Designed:	
Ac	
Dielectric Withstanding Voltage In Volts:	
2300.0	
Overall Length:	
5.710 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
3.380 inches	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
3.380 inches	
Overall Height:	
4.330 inches	
Overall Width:	
4.330 inches	
Mounting Hole Diameter:	
0.312 inches	
Scale Division Quantity:	
50 single indicator single range	
Frequency Rating:	
Between 55.0 hertz and 65.0 hertz	
Environmental Protection:	
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibrat	ion I
water resistant	
Furnished Items And Quantity:	
Nut 6; lockwasher 6; seal 1	
Indicator Type:	
Dial w/pointer	
Installation Design:	
Panel	
Mounting Arrangement Style:	
Four hole/stud rectangular/square	
Dial Scale Marking Color:	
Black single indicator single range	
Accuracy In Percent:	
-0.15/+0.15 at full scale single indicator single range	
Meter Depth Behind Mounting Flange:	
3.790 inches	
Meter Body Diameter Behind Mounting Flange:	
3.970 inches	
Movement Type:	
Moving coil, permanent magnet	
Background Color:	

Electrical Frequency Meter - Page 2 of 2



**Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Linear single indicator single range **Measurement Range:** +55.0/+65.0 hertz single indicator single range **Scale Selection Method:** Terminal **Features Provided:** Zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Plastic acrylic **Special Test Features:** Complies with mil-m-10304 Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A310a0