

View Online at <https://aerobasegroup.com/nsn/6625-01-275-9328>

Circuit Current For Which Designed:

Ac

Overall Length:

5.000 inches

Overall Height:

1.890 inches

Overall Width:

4.390 inches

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Environmental Protection:

Heat resistant and splash proof

Indicator Type:

Digital display

Installation Design:

Panel

Meter Depth Behind Mounting Flange:

4.000 inches

Meter Body Width Behind Mounting Flange:

3.700 inches

Power Source:

External

Mounting Facility Type And Quantity:

2 clip

Display Type:

Light emitting diode

Display Digit Quantity:

4-1/2

Measurement Range:

-19.999/+19.999 volts single indicator single range

Meter Body Height Behind Mounting Flange:

1.320 inches

Features Provided:

Electrical overload protection

Accuracy Rating:

Porm 0.01 pct of reading porm 0.005 pct of range single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 connector, plug

Operating Voltage Rating In Volts:

Between 115.0 ac and 230.0 ac

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Specification Data:

10855-wss96336 manufacturers specification control

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0