

View Online at <https://aerobasegroup.com/nsn/6625-01-276-2534>

**Overall Length:**

2.375 inches

**Overall Height:**

0.625 inches

**Overall Width:**

1.840 inches

**Frequency Rating:**

Between 400.0 megahertz and 800.0 megahertz

**Voltage Standing Wave Ratio:**

1.30

**Insertion Loss In Decibels:**

1.0

**Power Rating:**

1.0 watts peak

**Special Features:**

Corrosion resistant metals and corrosion resistant ferrous alloys, enamel; four 0.136 in. Diameter mounting holes on 2.000 in. By 0.620 in. Mounting centers; one input and four output female sma connectors; four way power division; split: m6 db nom; output port isolation: 30 db; phase balance: porm 2.0 deg; impedance: 50 ohms; phase slope linear: porm 1 deg; amplitude balance: 0.2 db max; metallic shield enclosure; operating temp range: 0 to 60 degrees c; storage temp range: m62 to 75 degrees c; altitude pressure: 50000 feet; temp shock resistant: m55 to 85 degrees c; humidity, shock and vibration resistant

**Precious Material And Location:**

Connector surfaces gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A512n0