

View Online at <https://aerobasegroup.com/nsn/6625-01-276-5676>

Circuit Current For Which Designed:

Dc

Overall Length:

1.352 inches

Overall Height:

1.100 inches

Overall Width:

2.500 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.470 inches

Barrel Width:

1.000 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.830 inches

Meter Body Width Behind Mounting Flange:

2.350 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

2.060 inches

Meter Barrel Depth:

0.830 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 quick disconnect, male

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0