## NSN 6625-01-276-8824

Special Scale Meter - Page 1 of 2

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-01-276-8824

AC
Overall Length:
6.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
7.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
9.875 inches
Overall Height:
11.000 inches
Overall Width:
9.000 inches
Mounting Hole Diameter:
0.406 inches
Scale Division Quantity:
120 single indicator single range
Environmental Protection:
Corrosion resistant and dust resistant and humidity resistant and vibration resistant and water resistant
Furnished Items And Quantity:
Nut 4; seal 1; lamp 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
White single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range
Pointer Color:
White single indicator single range
Scale Marking:
60; 50; 40; 30; 20; 10; 0; 10; 20; 30; 40; 50; 60; port; stbd; rate of turn; degrees per min

Scale Graduation Type:

4 screw and 4 unthreaded hole

Linear single indicator single range

**Mounting Facility Type And Quantity:** 

## NSN 6625-01-276-8824

Special Scale Meter - Page 2 of 2



Features Provided:
Self-illumination facility
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 solderless lug
Operating Voltage Rating In Volts:
115.0 ac
Material:
Aluminum
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel and paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular surface mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0