

View Online at <https://aerobasegroup.com/nsn/6625-01-276-8824>

Circuit Current For Which Designed:

Ac

Overall Length:

6.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

9.875 inches

Overall Height:

11.000 inches

Overall Width:

9.000 inches

Mounting Hole Diameter:

0.406 inches

Scale Division Quantity:

120 single indicator single range

Environmental Protection:

Corrosion resistant and dust resistant and humidity resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 4; seal 1; lamp 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

60; 50; 40; 30; 20; 10; 0; 10; 20; 30; 40; 50; 60; port; stbd; rate of turn; degrees per min

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solderless lug

Operating Voltage Rating In Volts:

115.0 ac

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel and paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0