

View Online at <https://aerobasegroup.com/nsn/6625-01-278-5138>

**Width:**

21.000 inches

**Length:**

23.000 inches

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

60.0 hertz

**End Application:**

An/aaq-15 and an/aaq-17

**Electrical Power Source Relationship:**

Operating

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Performance testing, fault isolation, performance verification; precision alignment of the azimuth; power and signal interface and test signal interface; mechanical rate simulation and mechanical interface

**Special Features:**

Includes transit case, a hp-2600a multimeter, a genisco 1102 rate table, lambda +5 and +/-15 vdc power supplies, 2 circuit cards, gyro power supply 96214-2439735-1 and gyro capture loop 96214-2439469-1 (mod); case not weather resistant; controls and indicators include: power on-off, power indicator, board select (internal-external gyro power supply), azimuth rate null adjust, elevation rate null adjust, gyro signal (azimuth-elevation), dmm select, capture loop test, gyro test signal, board select, test points

**Functional Description:**

TEST-GY-ROS-COPE

**Height:**

18.000 inches

**Supplementary Features:**

Manufacturers name: gyroscope alignment and test assembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a