

View Online at <https://aerobasegroup.com/nsn/6625-01-278-8133>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

1.063 inches

Overall Diameter:

2.219 inches

Environmental Protection:

Cold resistant and corrosion resistant and dustproof and heat resistant and sand proof and shock resistant and submersible and vibration resistant and watertight and windproof

Distance Between Mounting Facility Centers:

1.000 inches

Furnished Items And Quantity:

Nut 4; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-10.0/+10.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.750 inches

Meter Body Diameter Behind Mounting Flange:

2.031 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-50.0/+50.0 amperes single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Electrostatic shield

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Mtg studs are term.

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets mil-a-3427 tests

Style Designator:

Round flush mtg

Supplementary Features:

Silicone dampened response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0