

View Online at <https://aerobasegroup.com/nsn/6625-01-279-8062>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.251 inches

Overall Diameter:

Between 1.235 inches and 1.265 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.901 inches

Meter Body Diameter Behind Mounting Flange:

Between 0.985 inches and 1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+60.0 watts single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize and paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Specification Data:

80063-sm-a-947038 manufacturers specification control

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0