NSN 6625-01-279-8064

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-279-8064

Overall Length:
1.890 inches
Overall Height:
0.390 inches
Overall Width:
1.305 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Irregular
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Storage Type:
General purpose warehouse
Circuit Construction Type:
Solid state
Frequency Per Channel:
4.0 gigahertz input channel err-100 and 18.0 gigahertz input channel err-100
Attenuation In Decibels:
7.5
Average Power Rating Per Channel:
300.0 milliwatts input
Impedance Rating Per Channel:
50.000 ohms operating channel
Connection Type And Location:
Receptacle, coaxial front and receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
3 receptacle, coaxial external
Special Features:
Sma jack rf connectors
Functional Description:
Combines modulated and local rf signals to produce a modulated if signal
Cognizant Service:

Usaf

NSN 6625-01-279-8064

Frequency Mixer Stage - Page 2 of 2



Special	Marking	S
----------------	---------	---

Lo and rf ports marked I and r respectively; if port marked x

Special Test Features:

Environmentals per mil-std-202

Supplementary Features:

Acceleration and thermal shock resistant

Type/model Designation:

Mdc-171

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200