

View Online at <https://aerobasegroup.com/nsn/6625-01-281-1694>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

6.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Mounting Hole Diameter:

0.312 inches

Scale Division Quantity:

75 single indicator single range

Environmental Protection:

Shock resistant and watertight

Furnished Items And Quantity:

Nut 12; washer 24

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

5.312 inches

Meter Body Diameter Behind Mounting Flange:

3.938 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+25000.0 kilowatts single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Electrical overload protection and magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

8 threaded stud

Special Features:

Transformer rated

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-19088

Style Designator:

Rectangular flush mtg

Supplementary Features:

M 20 to p 65 degrees c operating temp range

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0