

View Online at <https://aerobasegroup.com/nsn/6625-01-281-4004>

Circuit Current For Which Designed:

Dc

Overall Length:

2.460 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.770 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.770 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Mounting Hole Diameter:

0.116 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Cold resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 4; flat washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+45.000/+65.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.730 inches

Meter Body Diameter Behind Mounting Flange:

2.070 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+45.0/+65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Screw for ground wire on back

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Zinc

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0