

View Online at <https://aerobasegroup.com/nsn/6625-01-281-6631>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

3.969 inches

Overall Width:

3.969 inches

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.563 inches

Furnished Items And Quantity:

Nut 8; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.500 inches

Meter Body Diameter Behind Mounting Flange:

3.781 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+45.0/+65.0 hertz single indicator single range

Mounting Stud Diameter:

0.138 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Phase:

Single

Special Features:

High torque to weight ratio

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets ansi c-39.1 requirements

Style Designator:

Rectangular flush mtg

Supplementary Features:

12 ounce net weight

Unit Of Issue Weight:

3.00 pounds

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0