

View Online at <https://aerobasegroup.com/nsn/6625-01-282-2111>

Circuit Current For Which Designed:

Ac

Overall Length:

8.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.500 inches

Overall Width:

4.500 inches

Mounting Hole Diameter:

0.313 inches

Scale Division Quantity:

50 single indicator single range

Frequency Rating:

60.0 hertz

Environmental Protection:

Cold resistant and dustproof and heat resistant and water resistant and windproof

Furnished Items And Quantity:

Nut 8; washer 8

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.125/+0.125 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

6.500 inches

Meter Body Diameter Behind Mounting Flange:

3.906 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and nonglare glass and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to ansi c39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

Self contained transducer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0