NSN 6625-01-283-6191

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-283-6191

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
500.0
Overall Length:
7.760 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 6.045 inches and 6.055 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 0.720 inches and 0.730 inches
Overall Height:
1.510 inches
Overall Width:
6.690 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
25 single indicator single range
Environmental Protection:
Dripproof and heat resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Washer 16; nut 8
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
20.0 milliamperes
Dial Scale Marking Color:
Black, dull single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
Between 5.750 inches and 5.840 inches
Meter Body Width Behind Mounting Flange:
5.430 inches
Movement Type:
Moving coil, permanent magnet

NSN 6625-01-283-6191

Special Scale Meter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
White single indicator single range
Scale Marking:
Feet; 15; 20; 25; 30; 35; 40
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Meter Body Height Behind Mounting Flange:
1.190 inches
Features Provided:
Magnetic shield and nonglare glass and rfi shielding and self-illumination facility and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 threaded stud
Special Features:
Two term. Provide 28 vdc for red illumination on pointer against translucent background
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Conforms to mil-m-10304
Style Designator:
Rectangular flush mtg
Supplementary Features:
10 ohm maximum coil resistance
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0