

View Online at <https://aerobasegroup.com/nsn/6625-01-284-0533>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2300.0

**Overall Length:**

5.710 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.380 inches

**Overall Height:**

4.330 inches

**Overall Width:**

4.330 inches

**Scale Division Quantity:**

60 single indicator single range

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant and water resistant and windproof

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

5.0 amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.790 inches

**Meter Body Diameter Behind Mounting Flange:**

3.970 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+600.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Criticality Code Justification:**

Mark

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Phase:**

Single

**Special Features:**

Ruggedized

**Special Markings:**

Red line at 450 v

**Material:**

Plastic and steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with specification ansi c-39.1

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Ground detector type

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0