

View Online at <https://aerobasegroup.com/nsn/6625-01-284-0533>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2300.0

Overall Length:

5.710 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Scale Division Quantity:

60 single indicator single range

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Mounting Stud Length:

0.625 inches

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant and water resistant and windproof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

5.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.790 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+600.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Criticality Code Justification:

Mark

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Features:

Ruggedized

Special Markings:

Red line at 450 v

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Complies with specification ansi c-39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

Ground detector type

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0