## NSN 6625-01-284-1521

Ammeter - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/6625-01-264-1521
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2300.0
Overall Length:
5.710 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.380 inches
Overall Height:
4.330 inches
Overall Width:
4.330 inches
Scale Division Quantity:
50 single indicator single range
Frequency Rating:
Between 40.0 hertz and 70.0 hertz
Mounting Stud Length:
0.625 inches
Environmental Protection:
Humidity resistant and shock resistant and vibration resistant and water resistant and windproof
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
5.0 amperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
3.790 inches
Meter Body Diameter Behind Mounting Flange:
3.970 inches
Movement Type:
Moving coil, permanent magnet

**Background Color:** 

White single indicator single range

## NSN 6625-01-284-1521

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+5000.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Transformer and zero adjuster
Criticality Code Justification:
Mark
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
Red line at 4000 amp
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0