

View Online at <https://aerobasegroup.com/nsn/6625-01-284-1524>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.874 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.874 inches

Overall Height:

2.370 inches

Overall Width:

2.370 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.530 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.450 inches

Meter Body Diameter Behind Mounting Flange:

2.180 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

X 100; 5; 0; 5

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0