## NSN 6625-01-284-4614

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-284-4614

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
500.0
Overall Length:
7.760 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 6.045 inches and 6.055 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 0.720 inches and 0.730 inches
Overall Height:
1.510 inches
Overall Width:
6.690 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
50 single indicator single range
Environmental Protection:
Dripproof and heat resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Washer 16; nut 8
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
20.0 milliamperes
Dial Scale Marking Color:
Black, dull single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
Between 5.750 inches and 5.840 inches
Meter Body Width Behind Mounting Flange:
5.430 inches
Movement Type:
Moving coil permanent magnet

Moving coil, permanent magnet

## NSN 6625-01-284-4614

Arbitrary Scale Meter - Page 2 of 2



## **Background Color:** White single indicator single range **Pointer Color:** White single indicator single range Scale Marking: 0; 20; 40; 60; 80; 100 Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Linear single indicator single range Meter Body Height Behind Mounting Flange: 1.190 inches **Features Provided:** Magnetic shield and nonglare glass and rfi shielding and self-illumination facility and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 4 threaded stud **Special Features:** Two term. Provide 28 vdc for red illumination on pointer against translucent background Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint **Special Test Features:** Conforms to mil-m-10304 Style Designator: Rectangular flush mtg **Supplementary Features:** 10 ohm maximum coil resistance **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A310a0