

View Online at <https://aerobasegroup.com/nsn/6625-01-290-1922>

**Circuit Current For Which Designed:**

Ac or dc

**Overall Depth:**

2.200 inches

**Overall Length:**

8.000 inches

**Overall Width:**

3.750 inches

**Environmental Protection:**

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Spare fuse 1; operator manual 1

**Indicator Type:**

Digital display and bargraph

**Installation Design:**

Bench or hand held

**Power Source:**

Internal

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

3.5

**Measurement Range:**

+0.0/+3200.0 microamperes, dc single indicator 6th range

**Scale Selection Method:**

Switch and terminal

**Features Provided:**

Autoranging and electrical overload protection and internal battery accommodation and portable and warning feature

**Criticality Code Justification:**

Zzzy

**Accuracy Rating:**

Prom 1.5 pct of reading plus 2 digits single indicator 5th range

**Display Color:**

Black single indicator all ranges

**Circuit Attachment Method And Quantity:**

2 clip and 2 wire lead

**Operating Voltage Rating In Volts:**

9.0 ac

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard lo4040

**Material:**

Plastic

**Style Designator:**

Portable

**Supplementary Features:**

Hold button to capture and display readings; 31 segment bar graph for peaking, nulling, capacitor checking

**Fsc Application Data:**

Test set, elect. Equip.

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be iaw naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0