

View Online at <https://aerobasegroup.com/nsn/6625-01-290-1922>

Circuit Current For Which Designed:

Ac or dc

Overall Depth:

2.200 inches

Overall Length:

8.000 inches

Overall Width:

3.750 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Spare fuse 1; operator manual 1

Indicator Type:

Digital display and bargraph

Installation Design:

Bench or hand held

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

3.5

Measurement Range:

+0.0/+3200.0 microamperes, dc single indicator 6th range

Scale Selection Method:

Switch and terminal

Features Provided:

Autoranging and electrical overload protection and internal battery accommodation and portable and warning feature

Criticality Code Justification:

Zzzy

Accuracy Rating:

Prom 1.5 pct of reading plus 2 digits single indicator 5th range

Display Color:

Black single indicator all ranges

Circuit Attachment Method And Quantity:

2 clip and 2 wire lead

Operating Voltage Rating In Volts:

9.0 ac

Special Features:

Item must comply with requirements of defense supply center columbus production standard lo4040

Material:

Plastic

Style Designator:

Portable

Supplementary Features:

Hold button to capture and display readings; 31 segment bar graph for peaking, nulling, capacitor checking

Fsc Application Data:

Test set, elect. Equip.

Reference Number Differentiating Characteristics:

Reference number differentiating material will be iaw naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0