

View Online at <https://aerobasegroup.com/nsn/6625-01-290-2447>

Circuit Current For Which Designed:

Dc

Overall Length:

0.720 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches

Overall Height:

3.550 inches

Overall Width:

4.550 inches

Mounting Stud Length:

0.500 inches

Environmental Protection:

Cold resistant and heat resistant

Furnished Items And Quantity:

Nut 4; washer 8

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Background Color:

Black single indicator single range

Scale Marking:

Displays all increments between m 2000 and p 2000

Mounting Facility Type And Quantity:

4 threaded stud

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Mounting Stud Diameter:

0.138 inches

Features Provided:

Nonglare glass and transformer

Accuracy Rating:

Porm 0.05 pct of full scale porm 1 count single indicator single range

Display Color:

White single indicator single range

Circuit Attachment Method And Quantity:

5 screw

Operating Voltage Rating In Volts:

Between 7.0 dc and 12.0 dc

Special Features:

200 ohm impedance

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular surface mtg

Supplementary Features:

Flame retardant pcb

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0