

View Online at <https://aerobasegroup.com/nsn/6625-01-291-0595>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.306 inches and 1.318 inches

**Overall Height:**

Between 1.734 inches and 1.766 inches

**Overall Width:**

Between 1.734 inches and 1.766 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

30 single indicator 1st range

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

5.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+30.0 milliamperes, dc single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Internal shunting and magnetic shield and zero adjuster

**Circuit Attachment Method And Quantity:**

3 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Red line at 60 on 0 to 100 range and at 20 and 30 on 0 to 30 range; term. Marked: c, 30, 100

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304, type mr13m005dcmar

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

150 mv maximum power consumption

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0