

View Online at <https://aerobasegroup.com/nsn/6625-01-291-1402>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1800.0

Overall Length:

3.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.844 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.476 inches

Overall Height:

0.920 inches

Overall Width:

2.258 inches

Scale Division Quantity:

40 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1000.0 ohms

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+10.0 volts, dc single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Horizontal scale

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0