

View Online at <https://aerobasegroup.com/nsn/6625-01-292-1615>

Overall Length:

415.0 millimeters

Wattage Rating In Watts:

30.0

Overall Height:

88.0 millimeters

Overall Width:

212.0 millimeters

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 66.0 hertz

Internal Battery Accommodation:

Not included

Specific Usage Design:

Electronic test equipment

Voltage Rating:

100.0 volts or 120.0 volts or 220.0 volts or 240.0 volts

Unpackaged Unit Weight:

3.7 kilograms

Mounting Method:

Rack

Measurement Type:

Frequency and period average and ratio and time and time interval and totalizing

Frequency Range:

+1.0/+100.0 megahertz

Accuracy Rating:

Porm resolution porm time base error

Gate Time:

Between 60.0 microseconds and 10.0 seconds

Sensitivity Rating:

10.0 mv rms sine wave to 10.0 mhz; 25.0 mv rms sine wave to 100.0 mhz; 75.0 mv peak to peak pulse at pulse width of 5.0 ns

Ratio Display:

2.5 x period a)/gate time} x raratio

Internal Calibration Feature:

Not included

Display Type:

Light emitting diode

Display Digit Quantity:

8

Display Units Indicator:

Included

Display Positioned Decimal Point:

Not provided

Display Storage Facility:

Not included

Remote Control Provisions:

Not included

Solid State Feature:

Included

Inclosure Material And Location:

Metal case

Plug-in Units Provision:

Not included

Standard Frequency Output Feature:

Not included

Reference Data And Literature:

Hp 1990 product catalog

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T297-a