

View Online at <https://aerobasegroup.com/nsn/6625-01-296-4464>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

6.000 inches

Overall Length:

16.000 inches

Overall Width:

12.500 inches

Environmental Protection:

Waterproof

Indicator Type:

Bargraph

Installation Design:

Hand held

Display Type:

Liquid crystal

Measurement Range:

-40.0/+60.0 decibels above or below one milliwatt single indicator 1st range

Accuracy Rating:

Porm 12.5 khz single indicator 4th range

Display Color:

Black single indicator all ranges

Operating Voltage Rating In Volts:

110.0 ac and 12.5 dc

Special Features:

Weight 12 lbs; contains battery; internal broadband calibrator: freq 5-600 mhz, amplitude m 115 dbm/hz, accuracy porm 0.25 db; spectrum features: amplitude 10-30 db on screen, freq range: sweep high 50-550 mhz on screen, sweep low range 5-250 mhz on screen, zoom 4.5 mhz, 2-5 seconds screen update rate; display area 128 by 480 pixels, light electrouminescent, 9.5 by 2.5 in; memory capable; monitors fm audio, video, carrier-to-noise, system hum readings; includes software, shipping case, battery pack/charger and printer interface; type f connectors

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Portable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0