## NSN 6625-01-297-3308

Ammeter - Page 1 of 2

White single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-01-297-3308

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
5.230 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.310 inches
Overall Width:
4.310 inches
Frequency Rating:
Between 40.0 hertz and 70.0 hertz
Mounting Stud Length:
0.625 inches
Environmental Protection:
Shock resistant and vibration resistant
Furnished Items And Quantity:
Nut 12
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
5.0 amperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
3.380 inches
Meter Body Diameter Behind Mounting Flange:
3.970 inches
Movement Type:
Moving iron vane
Background Color:

## NSN 6625-01-297-3308

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0/+30.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Features Provided:
Transformer and zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
10 pin jack and 3 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Cadmium
Special Test Features:
Complies with ansi specification c-39.1
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0