

View Online at <https://aerobasegroup.com/nsn/6625-01-298-8089>

Circuit Current For Which Designed:

Dc

Overall Length:

69.5 millimeters

Overall Height:

144.0 millimeters

Overall Width:

144.0 millimeters

Scale Division Quantity:

75 single indicator single range

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

64.5 millimeters

Meter Body Width Behind Mounting Flange:

134.0 millimeters

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 2 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-750.0/+750.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

134.0 millimeters

Features Provided:

Transformer

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Range 200 v to 0 v to 200 v is limited

Special Markings:

Red mark left side 580 v, right side 560 v

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets din 57410/vde 0410 safety spec

Style Designator:

Rectangular flush mtg

Supplementary Features:

Increased vibration res

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0