

View Online at <https://aerobasegroup.com/nsn/6625-01-298-9494>

Circuit Current For Which Designed:

Ac

Overall Length:

74.5 millimeters

Overall Height:

144.0 millimeters

Overall Width:

144.0 millimeters

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

66.5 millimeters

Meter Body Width Behind Mounting Flange:

134.0 millimeters

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 2 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+45.0/+65.0 hertz single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

134.0 millimeters

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Operating Voltage Rating In Volts:

470.0 ac

Special Features:

3.5 va power consumption

Special Markings:

Red line at 62 hz

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets din 57410/vde 0410 safety spec

Style Designator:

Rectangular flush mtg

Supplementary Features:

Built-in measuring attachment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0