

View Online at <https://aerobasegroup.com/nsn/6625-01-299-1403>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

5.875 inches

Overall Height:

1.060 inches

Overall Width:

4.812 inches

Mounting Hole Diameter:

0.156 inches

Frequency Rating:

Between 58.0 hertz and 420.0 hertz

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

4.312 inches

Indicator Type:

Bargraph

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

200.0 microamperes

Meter Depth Behind Mounting Flange:

5.250 inches

Meter Body Width Behind Mounting Flange:

3.750 inches

Background Color:

Black single indicator single range

Scale Marking:

0 to 53 pounds x 1000

Mounting Facility Type And Quantity:

2 unthreaded hole

Display Type:

Light emitting diode

Meter Body Height Behind Mounting Flange:

0.730 inches

Features Provided:

Overranging and self-illumination facility

Accuracy Rating:

Form 1 pct of reading form 1 digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

6 threaded stud

Operating Voltage Rating In Volts:

Between 107.0 ac and 123.0 ac

Special Features:

Green led under and over voltage indication

Special Markings:

High voltage present, on warning label; test, at term.

Material:

Plastic

Style Designator:

Rectangular flush mtg

Supplementary Features:

Illumination controlled by 0 to 5 vrms signal

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0