

View Online at <https://aerobasegroup.com/nsn/6625-01-299-3724>

Circuit Current For Which Designed:

Ac

Overall Length:

69.0 millimeters

Overall Height:

96.0 millimeters

Overall Width:

96.0 millimeters

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

64.0 millimeters

Meter Body Width Behind Mounting Flange:

92.0 millimeters

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 2 screw

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+600.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

92.0 millimeters

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Resistant to tropical environment

Special Markings:

Red line

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

0.1 to 1.6 va power consumption

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0