

View Online at <https://aerobasegroup.com/nsn/6625-01-299-3728>

Circuit Current For Which Designed:

Ac

Overall Length:

76.0 millimeters

Overall Height:

96.0 millimeters

Overall Width:

96.0 millimeters

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

50.0 hertz

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

21

Meter Depth Behind Mounting Flange:

71.0 millimeters

Meter Body Width Behind Mounting Flange:

92.0 millimeters

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 2 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Meter Body Height Behind Mounting Flange:

92.0 millimeters

Circuit Attachment Method And Quantity:

2 binding post

Operating Voltage Rating In Volts:

Between 450.0 ac and 500.0 ac

Special Features:

Resistant to tropical environment

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

1 to 3 va power consumption

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0