

View Online at <https://aerobasegroup.com/nsn/6625-01-299-4535>

Circuit Current For Which Designed:

Dc

Overall Length:

2.420 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.990 inches and 4.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.552 inches and 3.572 inches

Overall Height:

4.180 inches

Overall Width:

4.730 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 2; washer 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.200 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-10.0/+10.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0