

View Online at <https://aerobasegroup.com/nsn/6625-01-300-6148>

Circuit Current For Which Designed:

Ac

Overall Length:

7.600 inches

Overall Height:

5.000 inches

Overall Width:

7.000 inches

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Indicator Type:

Digital display

Installation Design:

Bench

Display Type:

Light emitting diode

Measurement Range:

+0.0/+32.0 decibels single indicator single range

Accuracy Rating:

Porm 0.2 db single indicator single range

Display Color:

White single indicator single range

Operating Voltage Rating In Volts:

Between 115.0 ac and 230.0 ac

Special Features:

Input if freq 10-300 mhz, 100 khzsteps; if input 100 db; portable; receiving rf range 10 khz-95 ghz; noise source plus 28v, 25 db excess noise ratio; 8 pounds; linear output for x-y plotter

Functional Description:

Used to record transmitted/received secure voice signals; used to inspect/adjust critical signal to noise ratio of receiver units on an/gpn-12, airport surveillance radar

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0