

View Online at <https://aerobasegroup.com/nsn/6625-01-301-9829>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.990 inches and 4.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.552 inches and 3.572 inches

Overall Height:

4.410 inches

Overall Width:

4.850 inches

Scale Division Quantity:

80 single indicator single range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Dust resistant

Furnished Items And Quantity:

Mtg hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.210 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-400.0/+400.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets ansi c39.1 specifications

Style Designator:

Rectangular flush mtg

Supplementary Features:

Zero ctr scale

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0