

View Online at <https://aerobasegroup.com/nsn/6625-01-302-0484>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

70.2 millimeters

**Overall Height:**

48.0 millimeters

**Overall Width:**

48.0 millimeters

**Scale Division Quantity:**

60 single indicator single range

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Screw 2; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Frequency Response Range:**

+15.000/+65.000 hertz

**Sensitivity Rating:**

1.0 amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5/+1.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

65.2 millimeters

**Meter Body Width Behind Mounting Flange:**

Between 42.4 millimeters and 42.6 millimeters

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 clip

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+600.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

Between 42.4 millimeters and 42.6 millimeters

**Features Provided:**

Transformer and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 binding post

**Special Features:**

Spring loaded clamp on both sides; 1.2 times the full scale value for connection to current transformers

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0