

View Online at <https://aerobasegroup.com/nsn/6625-01-302-0891>

Circuit Current For Which Designed:

Ac

Overall Length:

70.2 millimeters

Overall Height:

48.0 millimeters

Overall Width:

48.0 millimeters

Scale Division Quantity:

25 single indicator single range

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Screw 2; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Frequency Response Range:

+15.000/+65.000 hertz

Sensitivity Rating:

1.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

65.2 millimeters

Meter Body Width Behind Mounting Flange:

Between 42.4 millimeters and 42.6 millimeters

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clip

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 amperes, ac single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

Between 42.4 millimeters and 42.6 millimeters

Features Provided:

Transformer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Spring loaded clamp on both sides; 1.2 times the full scale value for connection to current transformers

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0