

View Online at <https://aerobasegroup.com/nsn/6625-01-302-0893>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

67.0 millimeters

**Overall Height:**

96.0 millimeters

**Overall Width:**

96.0 millimeters

**Scale Division Quantity:**

50 single indicator single range

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Frequency Response Range:**

+0.040/+10.000 kilohertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-0.5/+0.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

62.0 millimeters

**Meter Body Width Behind Mounting Flange:**

88.0 millimeters

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 clamp and 1 flange and 2 screw

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+55.0/+65.0 hertz single indicator single range

**Meter Body Height Behind Mounting Flange:**

88.0 millimeters

**Features Provided:**

Transformer and zero adjuster

**Criticality Code Justification:**

Supp

**Circuit Attachment Method And Quantity:**

2 binding post

**Special Features:**

Quadrant scale

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

I/p freq 60 hz; rated 440 v

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0