

View Online at <https://aerobasegroup.com/nsn/6625-01-302-0893>

Circuit Current For Which Designed:

Ac

Overall Length:

67.0 millimeters

Overall Height:

96.0 millimeters

Overall Width:

96.0 millimeters

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Frequency Response Range:

+0.040/+10.000 kilohertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.5/+0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

62.0 millimeters

Meter Body Width Behind Mounting Flange:

88.0 millimeters

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 1 flange and 2 screw

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+55.0/+65.0 hertz single indicator single range

Meter Body Height Behind Mounting Flange:

88.0 millimeters

Features Provided:

Transformer and zero adjuster

Criticality Code Justification:

Supp

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Quadrant scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

I/p freq 60 hz; rated 440 v

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0