NSN 6625-01-303-3009

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-303-3009

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.890 inches
Overall Height:
0.500 inches
Overall Width:
2.200 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 2; lockwasher 2; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
2.100 inches
Meter Body Width Behind Mounting Flange:
2.000 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
1 snap slide
Scale Graduation Type:

Measurement Range: +1.0/+100000.0 microvolts, rf single indicator 2nd range

Nonlinear single indicator all ranges

NSN 6625-01-303-3009Multiple Scale Meter - Page 2 of 2



Scale Selection Method:
Terminal
Meter Body Height Behind Mounting Flange:
0.490 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
760 ohms for item
Special Markings:
On face, signal strength; line level
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Supplementary Features:
R-2368/urr, end item
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0