

View Online at <https://aerobasegroup.com/nsn/6625-01-303-3539>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

1.251 inches

Overall Diameter:

1.250 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Furnished Items And Quantity:

O ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

500.0 microamperes

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.901 inches

Meter Body Diameter Behind Mounting Flange:

1.000 inches

Movement Type:

Moving coil, permanent magnet

Power Source:

External

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Features Provided:

Electrostatic shield and magnetic shield and rfi shielding and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304, type mr05w500specr

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0