

View Online at <https://aerobasegroup.com/nsn/6625-01-303-3539>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Overall Length:**

1.251 inches

**Overall Diameter:**

1.250 inches

**Environmental Protection:**

Shock resistant and vibration resistant and watertight

**Furnished Items And Quantity:**

O ring 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

500.0 microamperes

**Accuracy In Percent:**

-3.0/+3.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

0.901 inches

**Meter Body Diameter Behind Mounting Flange:**

1.000 inches

**Movement Type:**

Moving coil, permanent magnet

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 threaded body and 1 threaded ring

**Features Provided:**

Electrostatic shield and magnetic shield and rfi shielding and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Conforms to mil-m-10304, type mr05w500specr

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0