NSN 6625-01-304-3347

Voltmeter - Page 1 of 2

Moving iron vane



View Online at https://aerobasegroup.com/nsn/6625-01-304-3347

01 - 110
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.550 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.570 inches
Overall Height:
4.200 inches
Overall Width:
4.660 inches
Mounting Stud Length:
0.660 inches
Environmental Protection:
Dust resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Nut 8; washer 8; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Frequency Response Range:
+25.000/+125.000 hertz
Sensitivity Rating:
250.0 volts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.340 inches
Meter Body Diameter Behind Mounting Flange:
2.690 inches
Movement Type:

NSN 6625-01-304-3347 Voltmeter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0/+250.0 volts, ac single indicator single range
Mounting Stud Diameter:
0.138 inches
Features Provided:
Knife edge pointer and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic phenolic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0