

View Online at <https://aerobasegroup.com/nsn/6625-01-304-8860>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

5.630 inches

Overall Height:

1.890 inches

Overall Width:

3.780 inches

Frequency Rating:

Between 1000.0 hertz and 2000.0 hertz

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Seal 1; strap1

Indicator Type:

Digital display

Installation Design:

Panel

Sensitivity Rating:

500.0 millivolts

Dial Scale Marking Color:

White single indicator single range

Meter Depth Behind Mounting Flange:

5.250 inches

Meter Body Width Behind Mounting Flange:

3.620 inches

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket

Display Type:

Light emitting diode

Display Digit Quantity:

4-1/2

Measurement Range:

+0.0/+500.0 millivolts, ac single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.770 inches

Features Provided:

Overranging

Accuracy Rating:

Porm 1 pct of reading plus 1 digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 printed circuit

Operating Voltage Rating In Volts:

115.0 ac

Phase:

Single

Special Features:

Ruggedized; automatic zero; rms calibration

Special Markings:

On back, one side marked + and other side marked -

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Supplementary Features:

100 ko min impedance

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0