

View Online at <https://aerobasegroup.com/nsn/6625-01-306-0339>

Circuit Current For Which Designed:

Ac

Overall Length:

74.0 millimeters

Overall Height:

96.0 millimeters

Overall Width:

96.0 millimeters

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

69.0 millimeters

Meter Body Width Behind Mounting Flange:

88.0 millimeters

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 2 screw

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+750.0 amperes, ac single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

88.0 millimeters

Features Provided:

Transformer and zero adjuster

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

1.2 times full scale value for conn to cur xfrmr

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Meets din 57410/vde 0410 safety spec

Style Designator:

Rectangular flush mtg

Supplementary Features:

Fault free between m25 and p 45 degrees c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0