

View Online at <https://aerobasegroup.com/nsn/6625-01-306-0339>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

74.0 millimeters

**Overall Height:**

96.0 millimeters

**Overall Width:**

96.0 millimeters

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

1.0 amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5/+1.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

69.0 millimeters

**Meter Body Width Behind Mounting Flange:**

88.0 millimeters

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 clamp and 2 screw

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+750.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

88.0 millimeters

**Features Provided:**

Transformer and zero adjuster

**Circuit Attachment Method And Quantity:**

2 binding post

**Special Features:**

1.2 times full scale value for conn to cur xfrmr

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Meets din 57410/vde 0410 safety spec

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Fault free between m25 and p 45 degrees c

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0