

View Online at <https://aerobasegroup.com/nsn/6625-01-307-9890>

Circuit Current For Which Designed:

Ac

Overall Length:

7.650 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Overall Height:

4.330 inches

Overall Width:

4.330 inches

Scale Division Quantity:

60 single indicator single range

Frequency Rating:

60.0 hertz

Mounting Stud Length:

0.625 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.220 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 300.0 amperes single indicator single range

Mounting Stud Diameter:

0.250 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

8 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Phase:

Three

Special Features:

Red lined at 200 kw; pt ratio 450-120; ct ratio 500-5

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0