

View Online at <https://aerobasegroup.com/nsn/6625-01-308-6344>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2300.0

**Overall Length:**

5.710 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.380 inches

**Overall Height:**

4.330 inches

**Overall Width:**

4.330 inches

**Frequency Rating:**

60.0 hertz

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Dust resistant and humidity resistant and shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.790 inches

**Meter Body Diameter Behind Mounting Flange:**

3.970 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-0.5/+0.5 power factor single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Features Provided:**

Transformer and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

120.0 ac

**Phase:**

Single

**Special Features:**

Ruggedized; 5 amperes rating

**Special Markings:**

Range from 0.5 to 1 to 0.5 power factor

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with ansi specification c-39.1

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Contains transducer

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0